Actions

MICROELECTRONICS Co., Ltd.

Actions-micro AM8360D Datasheet

Document Number: AM8360D Datasheet
Revision 1.0.0
Release date: 11/09/2021

Actions Microelectronics Co., Ltd.
701, 7floor, Golder Plaza, No.10 huayuandonglu, Haidian District,
Beijing, China

ACTIONS-MICRO DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, INCLUDING WITHOUT LIMITATION ANY AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND AGAINST INFRINGEMENT AND THE LIKE, AND ANY AND ALL WARRANTIES ARISING FROM ANY COURSE OF DEALING OR USAGE OF TRADE.

IN NO EVENT SHALL ACTIONS-MICRO BE RELIABLE FOR ANY DIRECT, INCIDENTAL, INDIRECT, SPECIAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES; OR FOR LOST DATA, PROFITS, SAVINGS OR REVENUES OF ANY KIND; REGARDLESS OF THE FORM OF ACTION, WHETHER BASED ON CONTRACT; TORT; NEGLIGENCE OF ACTIONS-MICRO OR OTHERS; STRICT LIABILITY; BREACH OF WARRANTY; OR OTHERWISE; WHETHER OR NOT ANY REMEDY OF BUYER IS HELD TO HAVE FAILED OF ITS ESSENTIAL PURPOSE, AND WHETHER ACTIONS-MICRO HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR NOT.


Memory sub system
512Mb DDR2 Memory Die with Controller
USB OTG
Multi-media sub system
H.264 Enecoder
JPEG Encoder
Video Compressor
Video Decompressor
Multi-media Transfer Schedule Manager
Display sub system
OSD
HDMI RX
Low speed interfaces

- ✓ **Transfer Schedule Manager**

- ✓ **MEMORY Storage**

- ✓ **DMA CONTROLLER**

- ✓ **Boot ROM**


- ✓ **USB 2.0 OTG**

- ✓ **OTHER INTERFACE**

- ✓ **POWER**

✓ PACKAGE

3 Power on Sequence




4 Pin Out Specification

PIN NUM	PIN NAME	Function
	HOSCI	
	HOSCO	
	AVCC2	
	VDD	
	EXT_R	
	AVDD33	
	RXCN_CH	
	RXCP_CH	
	RXON_CH	
	RXOP_CH	
	RX1N_CH	
	RX1P_CH	
	RX2N_CH	
	RX2P_CH	
	AVDD12	
	P_CECRX	
	P_I2C1SCL	
	P_I2C1SDA	
	VCC1	
	P_RESETB	
	P_UARTTX1	
	P_UARTRX1	
	P_MACRER	
	P_MACRVLD	
	P_MACMDIO	
	P_MACMDC	
	P_MACTVLD	
	P_MACTD1	
	P_MACTD0	
	P_MACTCLK	
	VCC0(2.5V)	
	P_MACRD1	
	P_MACRD0	
	P_MACTD2	
	P_MACTD3	

PIN NUM	PIN NAME	TYPE	Function

`H

4.1 Pin out diagram



5 Operating Conditions

SYMBOL	PARAMETER	RATING	UNITS

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS

6 Crystal Requirements

	±
	±